

## Navigator Digital

| Description        | Standard   | Unit                    | Values |      |      |      |      |     |     |     |
|--------------------|------------|-------------------------|--------|------|------|------|------|-----|-----|-----|
| Weight             | ISO 536    | gsm (g/m <sup>2</sup> ) | 80     | 90   | 100  | 120  | 135  | 160 | 250 | 300 |
| Thickness          | ISO 534    | microns (µm)            | 108    | 114  | 118  | 133  | 157  | 184 | 304 | 350 |
| Bulk               |            | mic/gsm                 | 1.35   | 1.27 | 1.18 | 1.04 | 1.17 |     |     |     |
| CIE Whiteness      | ISO 11475  | %                       | 169    |      |      |      |      |     |     |     |
| Opacity            | ISO 2471   | %                       | 95     | 96   | 97   | 98   |      | 99  | 100 | 100 |
| Roughness Bendtsen | ISO 8791/2 | ml/min                  | 150    |      | 100  | 50   | 150  |     |     |     |
| Moisture Content   | ISO 287    | %                       | 5.0    |      | 5.2  |      | 5.4  |     |     |     |

### Product Certifications

FSC®  
 EU Ecolabel  
 Chlorine free

### Mill Certifications

ISO 9001  
 ISO 14001  
 OHSAS 18001